SAFETY DATA SHEET

Date Revised: 11/14/03 Date Printed: 4/1/15 MANUFACTURER: SIERRA CORP/TK PRODUCTS EMERGENCY PHONE: 1-800-424-9300 ADDRESS : 11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223 MINNETONKA, MN 55343 NAME OF PREPARER : Safety Director PRODUCT NAME: EPOXY PATCH CATALYST, PART B PRODUCT CODE: TK-211 B HAZARD RISK CLASSIFICATION SIGNAL WORD: DANGER PICTOGRAM: GHS05 - CORROSION GHS07 - EXCLAMATION MARK GHS08 - HEALTH HAZARD GHS09 -ENVIRONMENT HAZARD CLASS HAZARD CATEGORY ACUTE TOXICITY CATEGORY 3 ORAL ACUTE TOXICITY CATEGORY 3 DERMAL CATEGORY 3 INHALATION ACUTE TOXICITY SKIN CORROSION / CATEGORY 1 IRRITATION SERIOUS EYE DAMAGE / CATEGORY 1 EYE IRRITATION RESPIRATORY SENSITIZER CATEGORY 1 SKIN SENSITIZER CATEGORY 1 CATEGORY 2 TOXIC TO REPRODUCTION TOXIC TO SPECIFIC TARGET ORGAN CATEGORY 3 TOXICITY - SINGLE EXPOSURE HAZARDOUS TO THE AQUATIC CHRONIC 2 ENVIRONMENT LONG-TERM (CHRONIC) HAZARD STATEMENTS: H301 Toxic if swallowed H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled H311 Toxic in contact with skin Causes severe skin burns and eye damage May cause allergic skin reaction Н314 Н317 Causes serious eye damage Toxic if inhaled Н318 н331 н334 May cause allergy or asthma symptoms or breathing difficulties if inhaled н335 May cause respiratory irritation н361 Suspected of damaging fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects PRECAUTIONARY STATEMENTS: PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and P201 P202 understood.

P231Handle and store contents under inert gas.P260Do not breath dusts/fume/gas/mist/vapors or spray.P264Wash hands and any exposed area thoroughly after handling.

P270 Do not eat, drink or smoke while using this product.

Date Revised: 11/14/03 Date Printed: 4/1/15 P271 Use only outdoors or in well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. P273 P281 Use appropriate personal protective impervious gloves/protective clothing/ OSHA approved eye protection/ face protection. In case of inadequate ventilation wear appropriate organic vapor P285 respiratory protection. **RESPONSE:** P301+P310 If swallowed: Immediately call a Poison Center / doctor. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice / attention. P308+P313 P310 Immediately call a POISON CENTER/doctor/ emergency responder. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see on this label) P322 Specific measures (see on this label) P330 Rinse mouth. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P342+P311 If experiencing respiratory symptoms: Call a Poison Center/doctor. P361+P363 Take off immediately all contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse. STORAGE : P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. DISPOSAL: P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations. WEIGHT EXPOSURE LIMITS CAS NUMBER PERCENT COMPONENT OSHA PEL ACGIH TLV OTHER _____ -----4-Nonyl Hydroxybenzene, Nonylphenol 84852-15-3 50 - 75 NOT ESTABLISHED * Polyethylenepolyamine Adduct 68953-36-6 25-50 NOT ESTABLISHED Aliphatic Amine 90-72-2 1-10 5 PPM (SKIN)

* Chemical(s) that are chronic health hazards. Refer to section 3 for further information.

80-05-7

112-57-2

3.7

1-10

1 PPM

300 MG/M3

1 PPM

+ Bisphenol A

* Tetraethylenepentamine

+ Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

PRIMARY ROUTES OF EXPOSURE:

Skin contact.

EFFECTS OF ACUTE EXPOSURE:

EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns.

SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts.

INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.

INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. Can cause gastrointestinal irritation, nausea, vomitting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

CHRONIC HEALTH EFFECTS:

Although some components may indicate chronic exposure effects, no effects are anticipated under normal use conditions due to the relatively low proportion in the total mixture.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

No known effects on other illnesses.

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION: If a large amount is ingested, give water or milk and induce vomitting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

 FLASH POINT: Greater than 200 F
 METHOD USED: PMCC

 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.4
 UPPER: n/a

 EXTINGUISHING MEDIA:
 UPPER: n/a

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communicatin Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

OTHER PRECAUTIONS:

All empty containers should be disposed of in an evironmentally safe manner in accordance with all governmental regulations.

RESPIRATORY PROTECTION: No special requirements under normal use conditions. In confined areas, or ares with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant. VENTILATION: General room ventilation is adequate. PROTECTIVE GLOVES: Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse. EYE PROTECTION: Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI 287.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible. WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidlines.

PHYSICAL STATE: Liquid ODOR: Amine or ammonia odor SPECIFIC GRAVITY (H2O=1): .97 BOILING RANGE: COATING V.O.C.: 0 g/l (0.0 lb/gl) COLOR: Various colors SOLUBILITY IN WATER: Dilutable VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than nBuAc

STABILITY:

Stable under normal conditions and handling.

CONDITIONS TO AVOID:

None known

INCOMPATIBILITY (MATERIALS TO AVOID):

Avoid exposure to strong oxidizing agents and reducing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

SENSITIZATION:

None known.

CARCINOGENICITY:

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard. REPRODUCTIVE TOXICITY:

_. . . .

There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:

There is no data to indicate that any component present at greater than 0.1% will alter DNA.

ENVIRONMENTAL DATA:

Contains ammonia or amines which may be toxic to aquatic life. Nonylphenol is a marine pollutant.

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

Date Printed: 4/1/15

Date Revised: 11/14/03

SHIPPING NAME:

UN3066, Paint, 8, III

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Subatances Control Act (TSCA) chemical substance inventory.

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 2.

STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE	
Bisphenol	80-05-7	CA, MA, NJ, PA	
	======SECTION	16 - OTHER I	NFORMATION ====================================
REVISION DATE:	11/14/03		
HMIS CODES: H	F	R P	
3	* 1	0 в	