

# SAFETY DATA SHEET

Page: 1 of 5  
Process Time: 2:49 pm

Date Revised: 6/1/11

Date Printed: 4/1/15

===== SECTION 1 - IDENTIFICATION =====

MANUFACTURER: SIERRA CORP/TK PRODUCTS      EMERGENCY PHONE: 1-800-424-9300  
ADDRESS : 11400 WEST 47TH STREET      INFORMATION PHONE: (952)938-7223  
MINNETONKA, MN 55343      NAME OF PREPARER : Safety Director

PRODUCT NAME: BRIGHT SEAL, CALIFORNIA  
PRODUCT CODE: TK-BR.SEAL CA

===== SECTION 2 - HAZARDS IDENTIFICATION =====

HAZARD RISK CLASSIFICATION

SIGNAL WORD: DANGER

PICTOGRAM:

GHS02 - FLAME    GHS07 - EXCLAMATION MARK

HAZARD CLASS

HAZARD CATEGORY

FLAMMABLE LIQUIDS	CATEGORY 2
ACUTE TOXICITY	CATEGORY 4 ORAL
ACUTE TOXICITY	CATEGORY 4 DERMAL
ACUTE TOXICITY	CATEGORY 4 INHALATION
SKIN CORROSION / IRRITATION	CATEGORY 2
SERIOUS EYE DAMAGE / EYE IRRITATION	CATEGORY 2 AND 2A
TOXIC TO SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	CATEGORY 3

HAZARD STATEMENTS:

H225            Highly flammable liquid and vapor  
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled  
H315            Causes skin irritation  
H319            Causes serious eye irritation.  
H335            May cause respiratory irritation  
H336            May cause drowsiness or dizziness

PRECAUTIONARY STATEMENTS:

PREVENTION:

P210            Keep away from heat/hot surfaces/sparks/open flames and other sources of ignition. No smoking.  
P233            Keep container tightly closed.  
P240            Ground and bond container and receiving equipment.  
P241            Use explosion-proof electrical / ventilation/lighting/handling equipment.  
P242            Use non-sparking tools.  
P243            Take action to prevent static discharge.  
P261            Avoid breathing dust/fume/gas/mist/vapor/ spray.  
P264            Wash hands and any exposed area thoroughly after handling.  
P270            Do not eat, drink or smoke while using this product.  
P271            Use only outdoors or in well-ventilated area.  
P280            Wear protective impervious gloves/ OSHA approved eye protection/face protection.

RESPONSE:

P301+P310      If swallowed: Immediately call a Poison Center / doctor.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower).

# SAFETY DATA SHEET

Date Revised: 6/1/11

Date Printed: 4/1/15

**P304+P340** If inhaled: Remove person to fresh air and keep comfortable for breathing.

**P305+P351+P338** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**P312** Call a POISON CENTER/doctor if you feel unwell.

**P321** Specific treatment (see on this label)

**P330** Rinse mouth.

**P332+P313** If skin irritation occurs: Get medical advice/attention.

**P337+P313** If eye irritation persists: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**P370+P378** In case of fire: Use carbon dioxide (CO<sub>2</sub>), powder, alcohol-resistant foam to extinguish.

**STORAGE:**

**P403+P233** Store in a well-ventilated place. Keep container tightly closed.

**P403+P235** Store in a well-ventilated place. Keep cool.

**P405** Store locked up.

**DISPOSAL:**

**P501** Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

===== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS =====

COMPONENT	CAS NUMBER	WEIGHT	EXPOSURE LIMITS		
		PERCENT	OSHA PEL	ACGIH TLV	OTHER
* Parachlorobenzotrifluoride	98-56-6	25-50		NOT ESTABLISHED	
+* 2-Propanone, Acetone	67-64-1	37.2		750 PPM	750 PPM 1000 PPM
+ 2-Butoxyethanol	111-76-2	1.1		25 PPM	25 PPM

\* Chemical(s) that are chronic health hazards. Refer to section 3 for further information.  
 + Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**PRIMARY ROUTES OF EXPOSURE:**

Skin contact, eye contact, and inhalation.

**EFFECTS OF ACUTE EXPOSURE:**

**EYES:** Contact with eyes may cause irritation including burning, watering, and redness.

**SKIN:** Contact may cause mild skin irritation including redness, burning, and drying and cracking of skin. Continued exposure may develop into dermatitis. Solvents can penetrate the skin and cause systematic effects similar to those under inhalation symptoms. 2-Butoxyethanol may be absorbed through skin and produce toxic effects similar to those resulting from inhalation exposure.

**INHALATION:** High vapor concentrations are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, asthma, drowsiness, unconsciousness, and other central nervous system effects, and possibly death.

**INGESTION:** Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.

**CHRONIC HEALTH EFFECTS:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (Sometimes referred to as Solvent or Painter's Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal. Chronic exposure may also cause damage to the respiratory system, lungs, eyes, skin, gastrointestinal tract, liver, spleen and kidneys. Repeated skin contact may cause persistent irritation or dermatitis.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:**

Conditions aggravated by exposure may include skin disorders, respiratory (asthma-like) disorders, and pre-existing

# SAFETY DATA SHEET

Page: 3 of 5  
Process Time: 2:49 pm

Date Revised: 6/1/11

Date Printed: 4/1/15

liver or kidney conditions.

## =====**SECTION 4 - FIRST AID MEASURES**=====

IF ON SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. If irritation develops and persists, seek medical attention.

IF IN EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower lids occasionally. If symptoms persist, seek medical attention.

If SWALLOWED: Do not induce vomiting. Immediately administer 1-2 glasses of water and contact a physician, hospital emergency room, or poison control center for further advice. Keep person warm, quiet and seek immediate medical attention. Aspiration of material into lungs can cause severe lung damage. VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

INHALATION: Move affected individual to fresh air. If breathing is difficult, qualified personnel should administer oxygen. If breathing has stopped give artificial respiration. If respiratory symptoms develop or persist, seek medical attention.

## =====**SECTION 5 - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: -15 F

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .9

UPPER: 12.8

### EXTINGUISHING MEDIA:

Foam, CO<sub>2</sub>, or dry chemical is recommended. Water spray is recommended to cool or protect exposed materials or structures.

### SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters. Carbon dioxide can displace oxygen, exercise caution when using CO<sub>2</sub> in confined areas.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors may be ignited by heat, sparks, flames, or other sources of ignition. Vapors are heavier than air and may travel considerable distances to a source of ignition where they may cause a flashback or explosion. If container is not properly cooled, it can rupture in the presence of excessive heat.

## =====**SECTION 6 - ACCIDENTAL RELEASE MEASURES**=====

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep all sources of ignition and hot metal surfaces away from spill/release. Use explosion-proof non-sparking equipment. Stay upwind from area. Isolate danger and keep unauthorized personnel out. Stop source of release if possible with minimal risk. Wear appropriate protective equipment including respiratory protection. Prevent spill from entering sewers, storm drains, or any other unauthorized treatment drainage systems and natural waterways by diking ahead of the spill. Spilled material may be absorbed with an appropriate spill kit. Notify fire authorities and appropriate federal, state, and local agencies if required.

## =====**SECTION 7 - HANDLING AND STORAGE**=====

### HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard.

Open container slowly to relieve any pressure. Bond and ground all equipment when transferring from one vessel to another. Static charge can accumulate by flow or agitation. Ignition can occur by static discharge. The use of explosion proof equipment is recommended and may be required. The use of respiratory protection is advised when concentrations exceed any established exposure limits and in confined spaces. Use good industrial and personal hygiene practice, wash thoroughly after handling, and do not wear contaminated clothing.

### STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

### OTHER PRECAUTIONS:

"Empty" containers retain residue, liquid and vapor, and may be dangerous. Do not cut, weld, pressurize, solder, drill,

# SAFETY DATA SHEET

Page: 4 of 5  
Process Time: 2:49 pm

Date Revised: 6/1/11

Date Printed: 4/1/15

grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause severe personal injury or death. All containers should be disposed of in an environmentally safe manner in accordance with all government regulations.

## =====**SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**=====

### **RESPIRATORY PROTECTION:**

Engineering or administrative controls should be implemented to reduce exposure. A NIOSH/MSHA approved respirator with an organic vapor cartridge should be used under conditions where airborne concentrations are expected to exceed exposure limits (See Section 2). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

### **VENTILATION:**

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

### **PROTECTIVE GLOVES:**

Prevent prolonged or repeated contact by wearing gloves impervious to solvents and other appropriate protective clothing. Launder contaminated clothing before reuse.

### **EYE PROTECTION:**

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

### **OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

### **WORK/HYGIENIC PRACTICES:**

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.

## =====**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**=====

**PHYSICAL STATE:** Liquid

**COLOR:** Clear (Water white)

**ODOR:** Hydrocarbon odor

**SOLUBILITY IN WATER:** Insoluble/Negligible

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** 1.02

**VAPOR DENSITY:** Heavier than air.

**BOILING RANGE:** 133 F - 336 F

**EVAPORATION RATE:** Faster than nBuAc

**COATING V.O.C.:** 94 g/l (0.78 lb/gal)

## =====**SECTION 10 - STABILITY AND REACTIVITY DATA**=====

### **STABILITY:**

Stable under normal conditions and handling.

### **CONDITIONS TO AVOID:**

All possible sources of ignition.

### **INCOMPATIBILITY (MATERIALS TO AVOID):**

Avoid exposure to strong oxidizing agents and reducing agents.

### **HAZARDOUS DECOMPOSITION OR BYPRODUCTS:**

Combustion may liberate toxic byproducts such as carbon dioxide, carbon monoxide, various oxides of carbon and nitrogen.

### **HAZARDOUS POLYMERIZATION:**

Will not occur.

## =====**SECTION 11 - TOXICOLOGICAL INFORMATION**=====

### **SENSITIZATION:**

None known.

### **CARCINOGENICITY:**

There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

### **REPRODUCTIVE TOXICITY:**

2-Ethoxyethanol has been suggested as a cause of male and female reproductive fertility effects, and testis damage.

### **TERATOGENICITY (BIRTH DEFECTS):**

There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

### **MUTAGENICITY:**

2-Butoxyethanol may cause blood disorders based on animal data.

## =====**SECTION 12 - ECOLOGICAL INFORMATION**=====

### **ENVIRONMENTAL DATA:**

Although no information is available for this specific product mixture, individual components may by themselves may have

# SAFETY DATA SHEET

Page: 5 of 5  
Process Time: 2:49 pm

Date Revised: 6/1/11

Date Printed: 4/1/15

ecological affects.

## SECTION 13 - DISPOSAL CONSIDERATIONS

This product is considered a RCRA hazardous waste due to the characteristic(s) of D001 (ignitability). Waste is subject to the land disposal restrictions in 40 CFR 268.40 and may require treatment standards. Consult state and local regulations to determine whether they are more stringent than the federal requirements.

Container contents should be completely used and containers empty prior to discarding. Container rinsate could be considered a RCRA hazardous waste and must be discarded in compliance with all applicable regulations. Larger empty containers, such as drums, should be returned to a professional drum reconditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal authorities.

## SECTION 14 - TRANSPORT INFORMATION

### SHIPPING NAME:

UN1139, Coating Solution, 3, II

## SECTION 15 - REGULATORY INFORMATION

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See section 2.

### STATE SPECIFIC REQUIREMENTS:

This product contains 2-Butoxyethanol, a chemical known to the state of California to cause reproductive harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS	CAS NUMBER	STATE CODE
2-Butoxyethanol	111-76-2	CA, FL, IL, MA, ME, MN, NJ, PA, RI

## SECTION 16 - OTHER INFORMATION

REVISION DATE: 06/01/11

HMIS CODES: H	F	R	P
2 *	3	0	I